

contact@pdx.gold
 503.783.6550
 pdx.gold
 20209 SW 95th Ave.
 Tualatin, OR 97062



CYCLONE DRY

All plant material contains moisture. During the extraction process, water vapor may be transferred with the solvent and damage your recovery pump; and/or freeze in your chiller and block the lines. The only way to stop this damage from occurring is a filter drier.

The CycloneDry family of filter driers will eliminate this problem, providing clean vapor solvent to pass through your pump. This occurs in two ways:

- 1) the CycloneDry acts as a cold trap, capturing liquid water at the bottom of the unit.
- 2) the vapor path forces the solvent THROUGH the filter media, removing any debris, and absorbing water vapor - cleaning and drying the solvent before reaching the recovery pump.



CycloneDry

CycloneDry MAX

CycloneDry MAX-XL

	Internal Volume	Empty Weight	Absorption Capacity
CycloneDry	310 in ³	29 lb	190 g
CycloneDry MAX	465 in ³	36 lb	285 g
CycloneDry MAX-XL	620 in ³	42 lb	380 g

FEATURES & SPECS

- Filtration: 40 microns
- Fittings: 1/2" tube fittings
- 150 PSI pressure relief valve (PRV)
- 3rd party certified
- Reusable filter cores: bake out in a vacuum oven
- Approved solvents: butane, propane & blends
- Pressure Range:
 - Minimum 30 in Hg
 - Maximum 150 psi

